not able to understand xa:map_match Posted by swapnilsurade - 2010/06/18 04:44 _____________________________________ Hi All, Please help me to understand the following syntax xa:map_match=xa-input::/ASDTCCFeedLoader/AUTOROUTEHEADER/SUBMITTINGHEADER Another one : xa:map_match=xa-results::CONTRAHEADER xa-results is used in another component as xa:copy=xa-results:: Understanding for xa:map_match is, it is used to match the value given in the xbc or xbd. In above 2 examples why xa-input and xa-results are used ? Thanks, swapnil == Re:not able to understand xa:map_match Posted by prichards - 2010/07/06 11:29 _____________________________________ The xa:map/xa:map_match instruction was originally designed for the XML Mapper BizComp (and subsequently the Multiformat BizComp) as a way to iterate through repeating XML structures and map results to the response. You can review the Designer Help to see how xa:map and xa:map_match are used in the BizComponent. (You will also find the xa:copy instruction in the documentation as well.) Although not documented as such, it has also been used as a BizDoc instruction to iterate through repeating structures, used in the same manner as in the BizComp, although there may be some limitations using this instruction in a BizDoc. The xa-input:: and xa-results:: references are XAware Axes, which are documented in the Designer Help -> Basic XAware Know How -> Path Expressions in Designer; you should review this section and the subsection, Understanding XPath and XAware Axes. In short, your first map match example matches all of the SUBMITTINGHEADER elements in the path expression from the InputXML passed into the BizComponent. Your second example matches all of the CONTRAHEADER elements from an intermediate processing result, most likely from another map match in order to process a nested repeating structure. ==
XAware Community Forums - XAware Community FireBoard Forum Component version: 1.0.4 Generated: 2 June, 2020, 03:58